


# optoSiC® SCANcoat 990-H

LOW-STRESS OPTICAL COATING OPTIMIZED FOR HIGH REFLECTIVITY AT **990NM** FOR AOI OF **45°** AND **37,5°**, RESPECTIVELY.



## 990-H

		TYPICAL VALUES	
Wavelength [ $\lambda_1$ ]	(nm)	900 - 1080	s. spectrum
Wavelength [ $\lambda_2$ ]	(nm)	632,8	
Scan Angle	(°)	41 ± 16	
HR [ $\lambda_1$ ] @45° u-pol	(%)	> 99,5	+/- 0,5%
R <sub>avg</sub> [ $\lambda_2$ ] @45 u-pol	(%)	> 70	+/- 2,5%
Powerdensity	[kW/cm²]	n.d.	LIDT* [@1064nm CW]
Damage Threshold / Energy Density	[J/cm²]	n.d.	for pulsed 1064nm radiation 10ns, 1 kHz

- Laser induced damage threshold (LIDT) is typically given as x-Watts per linear millimeter of beam radius (br) (1/e<sup>2</sup>) 310% at 45° Angle of Incidence.
- Transmission edges can vary ~ 2% from lot to lot for the given wavelength.
- All data given for ambient conditions 20-25°C, at higher temperatures thermal shifts will occur.
- Reflectivity is qualified on fused silica samples
- Measured uncertainty of HR +/- 1,0 %
- n.d. = not defined



**MERSEN Deutschland  
Holding GmbH & Co. KG**  
Division optoSiC

Baierbrunner Straße 39  
D-81379 Munich  
Germany

**phone** +49 (0) 89 780 7239 0  
**fax** +49 (0) 89 780 7239 211  
**email** info.munich@mersen.com

**www.optosic.com**  
**www.mersen.com**